

ZHENGZHOU ORIENT POWER CO., LTD

NO.9,Sanquan Road,Jinshui District,Zhengzhou,Henan, China Tel/Fax: +86 37186099969 direct: +86 13673997131 sales@composite-insulator.com http://www.compoite-insulator.com

72.5KV Composite post Insulator

Type: 72.5KV composite post insulator **Material:** Hard-wearing HTV silicone rubber

End Fittings: Hot-dip galvanized forged steel materials for end fittings give good performance on erosion

Specific mechanical failing load: 8kN.

Application: 72.5KV Composite post insulator is a kind of silicone rubber apparatus insulators or composite insulators. Its design consists of a resin impregnated fiberglass core, a polymeric housing and metallic end fitting attachment devices. 72.5KV composite post insulator can have many mechanical loading: compression, cantilever, tensile and/or torsion, depending on the application. We produce 4KN,6KN,8KN,10KN,12.5KN,16KN composite station post insulator.




Fig. 72.5KV 8KN Composite Post Insulator

Technical data:			
System voltage	72.5	kV	
Rated voltage	66	kV	
Creepage distance	2350	mm	
Specific mechanical cantilever load	8	kN	
Arcing distance	600	mm	
Total height	730	mm	
Lightning impulse withstand voltage	325	kV	
Power frequency dry withstand voltage	165	kV	
Power frequency wet withstand voltage	140	kV	
Color	Grey or red		
Standard	ANSI C29.9		
Package	Carton		